

# GMP Rotary Tablet Press Machine 2700 Series

## 1. Main application

The machine is a double-pressing automatically revolving piece-pressing machine which could make grain be pressed to be round piece, be carved characters special shapes and double color piece prescription. It is mainly used in manufacturing, food, electronics. (Note: when manufacturing double color piece, it only need replacing, components and adding powder absorbing apparatus which greatly lowers the cost and raises profit.

## 2. Features

- A. Machine meets GMP and Made in stainless steel. The inner tablet press surface already be special treated, which could keep surface luster and prevent from being polluted crossly.
- B. Equipped with transparent window which could help to observe the status of pressing tablet. Transparent window could be fully opened, Machine easy to clean and Maintenance. All monitors and operating components work well together.
- C. Machine speed could be adjusted
- D. Equipped with over-load protection apparatus. When pressure overloads, the machine will stop automatically
- E. Transmitting system is sealed in the oil box under the working area, which work separately. NO pollution and easy to send out heat and resist grinding.
- F. A power suction unit is attached ca rake the residual power during operation, so that the blockage powder can be collected and be reused.



**Silver Double Inc.**  
Website: [www.sidolim.com](http://www.sidolim.com)  
Email: [sale@sidolim.com](mailto:sale@sidolim.com)

[techservice@sidolim.com](mailto:techservice@sidolim.com)

### 3. Technique parameter

Model	2700A	2700B	2700C
Dies(sets)	23	25	27
Max.Pressure(Kn)	100	100	100
Max.Dia.of Tablet(mm)	45	40	30
Thickness of largest tablet (mm)	15	15	15
Max.Depth of Filling(mm)	30	30	30
Max.output of one-layer ablets(pcs/h)	69000	75000	81000
Rotational diameter(mm)	445	445	445
Rotational speed of revolving table(r/min)	10-25	10-25	10-25
Diameter of middle mould(mm)	52	52	52
Highness of middle mould(mm)	38	38	38
Length of up and down punch pole(mm)	45	45	45
Length of up punch pole(mm)	175	175	175
Length of down punch pole(mm)	180	180	180
Overall dimensions(mm)	1000*1250*1900	1000*1250*1900	1000*1250*1900
Net weight(kg)	3200	3200	3200
Motor (kW)	7.5	7.5	7.5
Voltage(V)	380	380	380

All products should be subjected to any change without notification.  
Please don't hesitate to contact us if have any questions.



**Silver Double Inc.**  
Website: [www.sidolim.com](http://www.sidolim.com)  
Email: [sale@sidolim.com](mailto:sale@sidolim.com)

[techservice@sidolim.com](mailto:techservice@sidolim.com)